6 FACCIN

2-Roll Plate Bending Machine with Urethane Roll



The HCU version 2-roll bending roll designed, built, and marketed by Faccin features a special construction system combined with a solid oversized structure which assures absolute precision and reliability, greater simplicity of the plate rolling process and maximum quality of the rolled product.

Every bending roll of Faccin's HCU series is configured with an urethane roll which, by exerting dynamic pressure, speeds up the plate forming process, assuring the best tolerances, and greatly simplifying the pre-bending-rolling-pre-bending sequences typical of 3-roll or 4-roll bending rolls.

Furthermore, the exclusive hydro-mechanical roll lifting system (GHS) assures positioning repeatability and constant working pressures.

Faccin's HCU series bending rolls with automation assure achieving precise tolerances with very fast processing times.

Therefore, they are the ideal solution for rolling medium and large batches of tubes with thickness up to 5mm and width up to 2 metres, achieving bending diameters of less than 80mm.

Datasheet

HCU

Productivityand Precision



The standard HCU machine can guarantee output levels of 180-200 pieces/hour while the special version HCU/S reaches output levels beyond 300 pieces/hour.

Also, the HCU standard bending roll version is a fully automatic machine and therefore does not require any manpower. Faccin's HCU 2-roll bending roll models are the best choice for anyone seeking high speed rolling machines able to assure high productivity and maximum precision in forming.





2-Roll Plate Bending Machine with Urethane Roll

 $\overline{\mathbf{A}}$

 $\overline{\mathbf{A}}$

Standard equipment

Lower roll in urethane for perfect pre-bending

Automatic processing cycle (5-20 sec)

Centralised lubrication

Special lower roll lifting system

Standard roll for minimum diameter Siemens Numerical Control for

automatic cycle control

Automatic release opening

Lubrication circuit

Emergency barrier around the machine

CE certified machine

Optional Features

Different sized spindle pipes

Spindle pipe support

Central support

Automatic working pressure adjustment

Interchangeable rolls

Automatic sheet loader

Automatic feeding and centring tables

Programmable back gauges
Automatic cylinder ejector

Automatic welding systems

Unloading station and conveyors

Datasheet

HCU



Productivity and Precision

Model/Size	550x3	550x4	550x5	670x3	1050x2	1050x3	1050x4	1250x3	1250x4	1550x3	1550x4	1550x5	2050x4
Plate width (mm)	520	520	520	650	1000	1000	1000	1200	1200	1500	1500	1500	2000
Prebending mild steel (mm)	3	4	5	3	2	3	4	3	4	3	4	5	4
Prebending stainless steel (mm)	2,5	3	3,5	2,5	1,5	2,5	3,5	2,5	3,5	2,5	3,5	4	3,5
Rolling Power (Hp)	7,5	7,5	7,5	7,5	7,5	7,5	7,5	10	12	15	15	15	20

[•] Special sizes and capacities available upon request. Please send us your inquiries.

[•] Data can be changed without prior notice in consideration of continuing technological improvements.